

Hash functions, program secrets and lattices

Giorgos Zirdelis

University of Maryland

giorgos@umd.edu

☰ Topic is lattice-based cryptography

- Hash Functions
- Program Obfuscation
- ...

💡 **Common theme:** Quest for "*universal*" tools

Cryptographic Hash Functions

Hash functions

- ▶ Hash functions are used **everywhere in cryptography**
 - **Both** in theory and practice
 - Hash-and-Sign, Merkle tree, **₿**, ...
- SHA-2, SHA-3
- Factoring
- Discrete Log
- Elliptic Curves
- Isogeny-based
- Lattice-based

Hash functions

► Hash functions are used **everywhere in cryptography**

- **Both** in theory and practice
- Hash-and-Sign, Merkle tree, **Bitcoin**, ...

○ SHA-2, SHA-3

○ Discrete Log

○ Isogeny-based

○ Factoring

○ Elliptic Curves

○ Lattice-based

Goal: Given h , find $x \neq x'$ **s.t.** $h(x) = h(x')$

Security: such x, x' **always** exist **but** are hard to find

Hash functions

- ▶ Hash functions are used **everywhere in cryptography**
 - **Both** in theory and practice
 - Hash-and-Sign, Merkle tree, **₿**, ...
- SHA-2, SHA-3
- Discrete Log
- Isogeny-based
- Factoring
- Elliptic Curves
- Lattice-based

Goal: Given h , find $x \neq x'$ **s.t.** $h(x) = h(x')$

Security: such x, x' **always** exist **but** are hard to find

- ▶ Which hash function is **most** secure?
Provably answer this, at least in theory?

Most secure?

- ▶ What does **most** secure mean for some \hat{h} ?

Most secure?

- ▶ What does **most** secure mean for some \hat{h} ?
- ▶ Collisions for \hat{h} must be **as hard**, as in **any other** h

Most secure?

- ▶ What does **most** secure mean for some \overline{h} ?
- ▶ Collisions for \overline{h} must be **as hard**, as in **any other** h
- ▶ Implies a **reduction**: $\forall h, h \leq \overline{h}$
 - for fixed **security parameter**
 - \overline{h} inherits hardness from **all** h

Most secure?

- ▶ What does **most** secure mean for some \overline{h} ?
- ▶ Collisions for \overline{h} must be **as hard**, as in **any other** h
- ▶ Implies a **reduction**: $\forall h, h \leq \overline{h}$
 - for fixed **security parameter**
 - \overline{h} inherits hardness from **all** h
- ▶ What are the reduction steps?

Reduction steps $h \rightarrow C_h \rightarrow \hat{h}$

Hash function h

Reduction steps $h \rightarrow C_h \rightarrow \hat{h}$

Hash function h

1. Represent h in a universal way (e.g. use boolean circuits)

- $h \rightarrow C_h$

Reduction steps $h \rightarrow C_h \rightarrow \overline{h}$

Hash function h

1. Represent h in a universal way (e.g. use boolean circuits)

- $h \rightarrow C_h$

2. Reduce C_h to a hash function \overline{h}

- $C_h \leq \overline{h}$

- Find collisions in $\overline{h} \implies$ Find collisions in $C_h, \forall h$

Reduction steps $h \rightarrow C_h \rightarrow \overline{h}$

Hash function h

1. Represent h in a universal way (e.g. use boolean circuits)

- $h \rightarrow C_h$

2. Reduce C_h to a hash function \overline{h}

- $C_h \leq \overline{h}$

- Find collisions in $\overline{h} \implies$ Find collisions in $C_h, \forall h$

3. Declare \overline{h} as the most secure (WC/AVG)

Reduction steps $h \rightarrow C_h \rightarrow \hat{h}$

Hash function h

1. Represent h in a universal way (e.g. use boolean circuits)

- $h \rightarrow C_h$

2. Reduce C_h to a hash function \hat{h}

- $C_h \leq \hat{h}$

- Find collisions in $\hat{h} \implies$ Find collisions in $C_h, \forall h$

3. Declare \hat{h} as the most secure (WC/AVG)

What should \hat{h} be?

In the 90s...

- ▶ The question about $\overset{\text{crown}}{h}$ was asked in [Papadimitriou '94]
...in the broader context of **total problems (TFNP)**
- ▶ It remained open, what $\overset{\text{crown}}{h}$ to use...
...it all starts with the **pigeonhole principle**

In the 90s...

- ▶ The question about $\overset{\text{crown}}{h}$ was asked in [Papadimitriou '94]
...in the broader context of **total problems (TFNP)**
- ▶ It remained open, what $\overset{\text{crown}}{h}$ to use...
...it all starts with the **pigeonhole principle**
- ▶ We use it to define hash functions, prior to the reduction

The pigeonhole principle – a reminder

Any function $h : [n] \rightarrow [m]$ with $n > m$ must have collisions

i.e. when $|\text{domain}| > |\text{range}|$

$$[n] = \{1, \dots, n\}$$

Define hash functions

- ▶ Define the set of **all** (poly-size) functions $h : [n] \rightarrow [m]$, with $n > m$

Define hash functions

- ▶ Define the set of **all** (poly-size) functions $h : [n] \rightarrow [m]$, with $n > m$
- ▶ i.e. all functions that **compress** their input
 - for convenience, we refer to these as **hash functions**

Define hash functions

- ▶ Define the set of **all** (poly-size) functions $h : [n] \rightarrow [m]$, with $n > m$
- ▶ i.e. all functions that **compress** their input
 - for convenience, we refer to these as **hash functions**
- ▶ compress input \rightarrow collisions exist 🐦🐦 \rightarrow **goal:** find collisions

Define hash functions

- ▶ Define the set of **all** (poly-size) functions $h : [n] \rightarrow [m]$, with $n > m$
- ▶ i.e. all functions that **compress** their input
 - for convenience, we refer to these as **hash functions**
- ▶ compress input \rightarrow collisions exist  \rightarrow **goal:** find collisions
- ▶ This set is the union of:
 1. Cryptographic hash functions (e.g. SHA-3, SIS)
 2. Non-cryptographic hash functions (e.g. pairwise independence)

Represent h – (step 1) – why circuits?

Want a universal way to represent any (poly-size) hash function h
(i.e. convenient to work with)

Represent h – (step 1) – why circuits?

Want a universal way to represent any (poly-size) hash function h
(i.e. convenient to work with)

- ▶ Be agnostic of groups, rings, fields, distributions, keys*, ...
- ▶ Represent every hash function h , in the same way

Represent h – (step 1) – why circuits?

Want a universal way to represent any (poly-size) hash function h
(i.e. convenient to work with)

- ▶ Be agnostic of groups, rings, fields, distributions, keys*, ...
- ▶ Represent every hash function h , in the same way
- ▶ Use the (poly-size) boolean circuit C_h that implements h

$$C_h : \{0, 1\}^n \rightarrow \{0, 1\}^m \quad \text{with } n > m \quad \text{👉👉}$$

n, m depend on the security parameter

* keys are hardcoded in C_h , i.e. C_{h_k} essentially

A subtle point

- ▶ By definition, $\{C_h\}$ includes **all** (poly-size) hash function circuits that map $\{0, 1\}^n \rightarrow \{0, 1\}^m$ with $n > m$
- ▶ **Even** for hash functions we might **have not discovered** yet!

A subtle point

- ▶ By definition, $\{C_h\}$ includes **all** (poly-size) hash function circuits that map $\{0, 1\}^n \rightarrow \{0, 1\}^m$ with $n > m$
- ▶ **Even** for hash functions we might **have not discovered** yet!

Note: we **do not** have to enumerate or explicitly know this set

The question in [Pap94] – (step 2)

- ▶ **Question:** Reduce C_h to a "natural" hash function \hat{h} ?
What is "natural" & why?

The question in [Pap94] – (step 2)

- ▶ **Question:** Reduce C_h to a "natural" hash function \hat{h} ?
What is "natural" & why?
- ▶ Circuits vs "everyday" problems
 - NP-Hard: Circuit-SAT \leq_p Subset-Sum, Clique, Vertex Cover, TSP
i.e. "natural" problems

The question in [Pap94] – (step 2)

- ▶ **Question:** Reduce C_h to a "natural" hash function \hat{h} ?
What is "natural" & why?
- ▶ Circuits vs "everyday" problems
 - NP-Hard: Circuit-SAT \leq_p Subset-Sum, Clique, Vertex Cover, TSP
i.e. "natural" problems
- ▶ Under every C_h maybe a "natural" \hat{h} like the Short Integer Solutions (SIS) is hidden...

The question in [Pap94] – (step 2)

- ▶ **Question:** Reduce C_h to a "natural" hash function \hat{h} ?
What is "natural" & why?
- ▶ Circuits vs "everyday" problems
 - NP-Hard: Circuit-SAT \leq_p Subset-Sum, Clique, Vertex Cover, TSP
i.e. "natural" problems
- ▶ Under every C_h maybe a "natural" \hat{h} like the Short Integer Solutions (SIS) is hidden...
- ▶ This would imply:

Finding collisions in any C_h reduces to finding Short Integer Solutions!

Goal in summary

$$\underbrace{h \longrightarrow C_h}_{\text{step 1 - easy}} \longrightarrow \overset{\text{crown}}{h}$$

Goal in summary

$$h \longrightarrow \underbrace{C_h \longrightarrow \overset{\text{crown}}{h}}_{\text{step 2 - reduction}}$$

Our results (almost there)

We reduce any hash function to an *almost* lattice problem, the **constrained Short Integer Solutions** problem (constrained-SIS)

- Sotiraki–Zampetakis–**Z** FOCS'18
- We believe the answer to be a lattice problem (ongoing work)
 $\stackrel{?}{\Rightarrow}$ lattice-based hash functions are the most secure
- We show the **first** [👑] h
- Solves open problem from [Pap94]
- Our reduction is worst-case

next: SIS reminder

The SIS problem [Ajtai '96, Micciancio-Regev '04]

- ▶ Given $\mathbf{A} \leftarrow \mathbb{Z}_q^{m \times n}$ with $n > m \log q$ (s.t. collisions exist)
- ▶ Find **distinct** $\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

The SIS problem [Ajtai '96, Micciancio-Regev '04]

- ▶ Given $\mathbf{A} \leftarrow \mathbb{Z}_q^{m \times n}$ with $n > m \log q$ (s.t. collisions exist)
- ▶ Find **distinct** $\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_1} = \boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_2} \pmod{q}$$

The SIS problem [Ajtai '96, Micciancio-Regev '04]

- ▶ Given $\mathbf{A} \leftarrow \mathbb{Z}_q^{m \times n}$ with $n > m \log q$ (s.t. collisions exist)
- ▶ Find **distinct** $\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_1} = \boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_2} \pmod{q}$$

...implies **short** $(\mathbf{x}_1 - \mathbf{x}_2) \in \{0, \pm 1\}^n$ s.t. $\mathbf{A}(\mathbf{x}_1 - \mathbf{x}_2) = \mathbf{0}$

The constrained-SIS problem

- ▶ Given $\mathbf{A} \in \mathbb{Z}_q^{m \times n}$ and semi-structured $\mathbf{G} \in \mathbb{Z}_q^{d \times n}$ with $n > (m + d) \log q$

The constrained-SIS problem

- ▶ Given $\mathbf{A} \in \mathbb{Z}_q^{m \times n}$ and semi-structured $\mathbf{G} \in \mathbb{Z}_q^{d \times n}$ with $n > (m + d) \log q$
- ▶ Find distinct $\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_1} = \boxed{\mathbf{A}} \cdot \boxed{\mathbf{x}_2} \pmod{q}$$

The constrained-SIS problem

- ▶ Given $\mathbf{A} \in \mathbb{Z}_q^{m \times n}$ and semi-structured $\mathbf{G} \in \mathbb{Z}_q^{d \times n}$ with $n > (m + d) \log q$
- ▶ Find distinct $\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{A} \cdot \mathbf{x}_1 = \mathbf{A} \cdot \mathbf{x}_2 \pmod{q}$$

$$\mathbf{G} \cdot \mathbf{x}_1 = \mathbf{G} \cdot \mathbf{x}_2 = \mathbf{0} \pmod{q}$$

constrained-SIS vs SIS

constrained-SIS (WC)

\mathbf{A} is arbitrary

\mathbf{G} is semi-structured

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{A}\mathbf{x}_1 = \mathbf{A}\mathbf{x}_2 \text{ and } \mathbf{G}\mathbf{x}_1 = \mathbf{0} = \mathbf{G}\mathbf{x}_2$$

SIS (AVG)

\mathbf{A} is uniformly random

–

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{A}\mathbf{x}_1 = \mathbf{A}\mathbf{x}_2$$

constrained-SIS vs SIS

constrained-SIS (WC)

\mathbf{A} is arbitrary

\mathbf{G} is semi-structured

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{Ax}_1 = \mathbf{Ax}_2 \text{ and } \mathbf{Gx}_1 = \mathbf{0} = \mathbf{Gx}_2$$

- unclear how to sample "most secure" keys

SIS (AVG)

\mathbf{A} is uniformly random

–

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{Ax}_1 = \mathbf{Ax}_2$$

- can sample keys
- unclear if SIS is the most secure
 h

constrained-SIS vs SIS

constrained-SIS (WC)

\mathbf{A} is arbitrary

\mathbf{G} is semi-structured

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{A}\mathbf{x}_1 = \mathbf{A}\mathbf{x}_2 \text{ and } \mathbf{G}\mathbf{x}_1 = \mathbf{0} = \mathbf{G}\mathbf{x}_2$$

- unclear how to sample "most secure" keys

SIS (AVG)

\mathbf{A} is uniformly random

–

$\mathbf{x}_1, \mathbf{x}_2 \in \{0, 1\}^n$ s.t.

$$\mathbf{A}\mathbf{x}_1 = \mathbf{A}\mathbf{x}_2$$

- can sample keys
- unclear if SIS is the most secure
h

Goal: (aka reduction)

1. **show** that constrained-SIS is a hash function
2. **reduce** any hash function to constrained-SIS

Goal: constrained-SIS is a hash function – pt1

Goal:

1. **show** that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

Goal: constrained-SIS is a hash function – pt1

Goal:

1. show that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

▶ \mathbf{A} and \mathbf{G} must compress their common input

Goal: constrained-SIS is a hash function – pt1

Goal:

1. show that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

- ▶ \mathbf{A} and \mathbf{G} must compress their common input
- ▶ \mathbf{A} is compressing, choice of params ✓

Goal: constrained-SIS is a hash function – pt1

Goal:

1. show that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

- ▶ \mathbf{A} and \mathbf{G} must compress their common input
- ▶ \mathbf{A} is compressing, choice of params ✓
- ▶ \mathbf{G} is compressing, choice of params...

Goal: constrained-SIS is a hash function – pt1

Goal:

1. show that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

- ▶ \mathbf{A} and \mathbf{G} must compress their common input
- ▶ \mathbf{A} is compressing, choice of params ✓
- ▶ \mathbf{G} is compressing, choice of params...
- ▶ ...but why should $\mathbf{G}\mathbf{x} = \mathbf{0}$?

Goal: constrained-SIS is a hash function – pt1

Goal:

1. show that constrained-SIS = (\mathbf{A}, \mathbf{G}) is a hash function

- ▶ \mathbf{A} and \mathbf{G} must compress their common input
- ▶ \mathbf{A} is compressing, choice of params ✓
- ▶ \mathbf{G} is compressing, choice of params...
- ▶ ...but why should $\mathbf{G}\mathbf{x} = \mathbf{0}$?
 - \mathbf{G} has structure ✓

The G in constrained-SIS

$$\mathbf{G} = \left(\begin{array}{cccc|cccc}
 \overbrace{1 \ 2 \ 4 \ \dots \ 2^\ell}^{\log q} & * & * & * & \dots & * & * & * & \dots & * \\
 0 & 1 & 2 & 4 & \dots & 2^\ell & \dots & * & * & * & \dots & * \\
 \vdots & & & & & & \ddots & & & & & \vdots \\
 0 & & & 0 & & & \dots & 1 & 2 & 4 & \dots & 2^\ell \\
 & & & & & & & & & & & \underbrace{* \ * \ * \ \dots \ *}_{n-d \log q}
 \end{array} \right)$$

- \mathbf{G} similar to the [gadget matrix](#) from [Micciancio-Peikert '12]

The G in constrained-SIS

$$\mathbf{G} = \left(\begin{array}{cccc|cccc}
 \overbrace{1 \ 2 \ 4 \ \dots \ 2^\ell}^{\log q} & * & * & * & \dots & * & * & * & \dots & * \\
 0 & 1 & 2 & 4 & \dots & 2^\ell & \dots & * & * & * & \dots & * \\
 \vdots & & & & & & \ddots & & & & & \vdots \\
 0 & & & 0 & & & \dots & 1 & 2 & 4 & \dots & 2^\ell \\
 & & & & & & & & & & & \underbrace{* \ * \ * \ \dots \ *}_{n-d \log q}
 \end{array} \right)$$

- ▶ \mathbf{G} similar to the [gadget matrix](#) from [Micciancio-Peikert '12]
- ▶ $\mathbf{G}\mathbf{x} = \mathbf{0}$ can [always](#) be satisfied by some $\mathbf{x} \in \{0, 1\}^n$

The G in constrained-SIS

$$\mathbf{G} = \left(\begin{array}{cccc|cccc}
 \overbrace{1 \ 2 \ 4 \ \dots \ 2^\ell}^{\log q} & * & * & * & \dots & * & * & * & \dots & * \\
 0 & 1 & 2 & 4 & \dots & 2^\ell & \dots & * & * & * & \dots & * \\
 \vdots & & & & & & \ddots & & & & & & \vdots \\
 0 & & & 0 & & & \dots & 1 & 2 & 4 & \dots & 2^\ell & \underbrace{* \ * \ * \ \dots \ *}_{n-d \log q}
 \end{array} \right) \cdot \begin{pmatrix} \dots \\ \dots \\ \dots \\ \{0, 1\} \\ \vdots \\ \{0, 1\} \end{pmatrix}$$

- ▶ \mathbf{G} similar to the [gadget matrix](#) from [Micciancio-Peikert '12]
- ▶ $\mathbf{G}\mathbf{x} = \mathbf{0}$ can [always](#) be satisfied by some $\mathbf{x} \in \{0, 1\}^n$
 - choose [last](#) $(n - d \log q)$ bits of \mathbf{x} [arbitrarily](#) (last row)...

The G in constrained-SIS

$$\mathbf{G} = \left(\begin{array}{cccc|cccc|cccc}
 \overbrace{1 \ 2 \ 4 \ \dots \ 2^\ell}^{\log q} & * & * & * & \dots & * & * & * & \dots & * & * & * & \dots & * \\
 0 & 1 & 2 & 4 & \dots & 2^\ell & \dots & * & * & * & \dots & * & * & * & \dots & * \\
 \vdots & & & & & & \ddots & & & & & & & & & & \\
 0 & & & 0 & & & \dots & 1 & 2 & 4 & \dots & 2^\ell & \underbrace{* \ * \ * \ \dots \ *}_{n-d \log q} & & & &
 \end{array} \right) \cdot \begin{pmatrix} \dots \\ \dots \\ \dots \\ \{0, 1\} \\ \vdots \\ \{0, 1\} \end{pmatrix}$$

- ▶ \mathbf{G} similar to the **gadget matrix** from [Micciancio-Peikert '12]
- ▶ $\mathbf{G}\mathbf{x} = \mathbf{0}$ can **always** be satisfied by some $\mathbf{x} \in \{0, 1\}^n$
 - choose **last** $(n - d \log q)$ bits of \mathbf{x} **arbitrarily** (last row)...
 - $\dots \mathbf{G}\mathbf{x} = \mathbf{0} \Leftrightarrow 1x_1 + 2x_2 + 4x_4 + \dots + 2^\ell x_{2^\ell} = - \boxed{* \ * \ * \ \dots \ *}$

The G in constrained-SIS

$$\mathbf{G} = \left(\begin{array}{cccc|cccc|cccc}
 \overbrace{1 \ 2 \ 4 \ \dots \ 2^\ell}^{\log q} & * & * & * & \dots & * & * & * & \dots & * & * & * & \dots & * \\
 0 & 1 & 2 & 4 & \dots & 2^\ell & \dots & * & * & * & \dots & * & * & * & \dots & * \\
 \vdots & & & & & & \ddots & & & & & & & & & & \\
 0 & & & 0 & & & \dots & 1 & 2 & 4 & \dots & 2^\ell & \underbrace{* \ * \ * \ \dots \ *}_{n-d \log q} & & & &
 \end{array} \right) \cdot \begin{pmatrix} \dots \\ \dots \\ \dots \\ \{0, 1\} \\ \vdots \\ \{0, 1\} \end{pmatrix}$$

► \mathbf{G} similar to the **gadget matrix** from [Micciancio-Peikert '12]

► $\mathbf{G}\mathbf{x} = \mathbf{0}$ can **always** be satisfied by some $\mathbf{x} \in \{0, 1\}^n$

- choose **last** $(n - d \log q)$ bits of \mathbf{x} **arbitrarily** (last row)...

- ... $\mathbf{G}\mathbf{x} = \mathbf{0} \Leftrightarrow 1x_1 + 2x_2 + 4x_4 + \dots + 2^\ell x_{2^\ell} = - \boxed{* \ * \ * \ \dots \ *}$

- rest of \mathbf{x} is **uniquely** determined using

backwards substitution & binary decomposition

an example with $d = 3, n = 10, q = 8$

$$\left(\begin{array}{ccc|ccc|ccc|c} 1 & 2 & 4 & 3 & 0 & 6 & 5 & 6 & 2 & 1 \\ 0 & 0 & 0 & 1 & 2 & 4 & 1 & 0 & 3 & 2 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 2 & 4 & 1 \end{array} \right) \cdot \begin{pmatrix} * \\ * \\ * \\ * \\ * \\ * \\ * \\ * \\ * \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} \pmod{8}$$

an example with $d = 3, n = 10, q = 8$

$$\left(\begin{array}{ccc|ccc|ccc|c} 1 & 2 & 4 & 3 & 0 & 6 & 5 & 6 & 2 & 1 \\ 0 & 0 & 0 & 1 & 2 & 4 & 1 & 0 & 3 & 2 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 2 & 4 & 1 \end{array} \right) \cdot \begin{pmatrix} * \\ * \\ * \\ * \\ * \\ * \\ * \\ x_7 \\ x_8 \\ x_9 \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} \pmod{8}$$

binary decomposition (last row)

$$1 \cdot x_7 + 2 \cdot x_8 + 4 \cdot x_9 + (1 \cdot 1) = 0 \pmod{8} \Rightarrow x_7 = x_8 = x_9 = 1$$

an example with $d = 3, n = 10, q = 8$

$$\left(\begin{array}{ccc|ccc|ccc|c} 1 & 2 & 4 & 3 & 0 & 6 & 5 & 6 & 2 & 1 \\ 0 & 0 & 0 & 1 & 2 & 4 & 1 & 0 & 3 & 2 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 2 & 4 & 1 \end{array} \right) \cdot \begin{pmatrix} * \\ * \\ * \\ x_4 \\ x_5 \\ x_6 \\ 1 \\ 1 \\ 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} \pmod{8}$$

binary decomposition (2nd row)

$$1 \cdot x_4 + 2 \cdot x_5 + 4 \cdot x_6 + \underbrace{(1 + 2 + 4 + 1)}_{\text{back substitution}} = 0 \pmod{8}$$

an example with $d = 3, n = 10, q = 8$

$$\left(\begin{array}{ccc|ccc|ccc|c} 1 & 2 & 4 & 3 & 0 & 6 & 5 & 6 & 2 & 1 \\ 0 & 0 & 0 & 1 & 2 & 4 & 1 & 0 & 3 & 2 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 2 & 4 & 1 \end{array} \right) \cdot \begin{pmatrix} x_1 \\ x_2 \\ x_3 \\ 1 \\ 0 \\ 0 \\ 1 \\ 1 \\ 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} \pmod{8}$$

binary decomposition (1st row)

$$1 \cdot x_1 + 2 \cdot x_2 + 4 \cdot x_3 + \underbrace{17}_{\text{back substitution}} = 0 \pmod{8}$$

an example with $d = 3, n = 10, q = 8$

$$\left(\begin{array}{ccc|ccc|ccc|c} 1 & 2 & 4 & 3 & 0 & 6 & 5 & 6 & 2 & 1 \\ 0 & 0 & 0 & 1 & 2 & 4 & 1 & 0 & 3 & 2 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 2 & 4 & 1 \end{array} \right) \cdot \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \\ 0 \\ 0 \\ 0 \\ 1 \\ 1 \\ 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix} \pmod{8}$$

Goal: constrained-SIS is a hash function – pt2

- ▶ $2^{n-d \log q}$ different values of \mathbf{x} can satisfy $\mathbf{G}\mathbf{x} = \mathbf{0}$
- ▶ same \mathbf{x} are mapped as: $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$

Goal: constrained-SIS is a hash function – pt2

- ▶ $2^{n-d \log q}$ different values of \mathbf{x} can satisfy $\mathbf{G}\mathbf{x} = \mathbf{0}$
- ▶ same \mathbf{x} are mapped as: $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$
- ▶ range of $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$ is q^m

Goal: constrained-SIS is a hash function – pt2

- ▶ $2^{n-d \log q}$ different values of \mathbf{x} can satisfy $\mathbf{G}\mathbf{x} = \mathbf{0}$
- ▶ same \mathbf{x} are mapped as: $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$
- ▶ range of $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$ is q^m
- ▶ $2^{n-d \log q} > q^m$

Goal: constrained-SIS is a hash function – pt2

- ▶ $2^{n-d \log q}$ different values of \mathbf{x} can satisfy $\mathbf{G}\mathbf{x} = \mathbf{0}$
- ▶ same \mathbf{x} are mapped as: $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$
- ▶ range of $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$ is q^m
- ▶ $2^{n-d \log q} > q^m \Rightarrow$ enough \mathbf{x} to have collisions in \mathbf{A}
i.e. $|\text{domain}| > |\text{range}|$

Goal: constrained-SIS is a hash function – pt2

- ▶ $2^{n-d \log q}$ different values of \mathbf{x} can satisfy $\mathbf{G}\mathbf{x} = \mathbf{0}$
- ▶ same \mathbf{x} are mapped as: $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$
- ▶ range of $\mathbf{x} \mapsto \mathbf{A}\mathbf{x}$ is q^m
- ▶ $2^{n-d \log q} > q^m \Rightarrow$ enough \mathbf{x} to have collisions in \mathbf{A}
i.e. $|\text{domain}| > |\text{range}|$

constrained-SIS is a hash function ✓

next: $C_h \leq$ constrained-SIS

Goal: $C_h \leq$ constrained-SIS

Reduce C_h to constrained-SIS

Goal: $C_h \leq$ constrained-SIS

Reduce C_h to constrained-SIS

Goal: Construct \mathbf{A}, \mathbf{G} out of C_h

Goal: $C_h \leq$ constrained-SIS

Reduce C_h to constrained-SIS

Goal: Construct \mathbf{A} , \mathbf{G} out of C_h

we start with \mathbf{G}

$C_h \leq$ constrained-SIS – the \mathbb{G} pt

- ▶ **Embed** C_h in \mathbb{G} using **OR** and **XOR** gates
 - Circuit gates in $C_h \rightarrow$ Linear equations in \mathbb{G}

$C_h \leq$ constrained-SIS – the G pt

► **Embed** C_h in G using **OR** and **XOR** gates

- Circuit gates in $C_h \rightarrow$ Linear equations in G

OR: $\boxed{x_1 \vee x_2} = y, z = x_1 \oplus x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$

XOR: $\boxed{x_1 \oplus x_2} = y, z = x_1 \wedge x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$

$C_h \leq$ constrained-SIS – the \mathbf{G} pt

► Embed C_h in \mathbf{G} using **OR** and **XOR** gates

- Circuit gates in $C_h \rightarrow$ Linear equations in \mathbf{G}

OR: $\boxed{x_1 \vee x_2} = y, z = x_1 \oplus x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$

XOR: $\boxed{x_1 \oplus x_2} = y, z = x_1 \wedge x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$

$$\mathbf{G} = \begin{pmatrix} \text{output gate} & \text{output wires} & 0 & 0 & 0 \\ 0 & \text{intermediate gate} & \text{intermediate wires} & 0 & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & \dots & \text{input gate} & \text{input wires} \end{pmatrix}$$

$C_h \leq$ constrained-SIS – the G pt

► **Embed** C_h in G using **OR** and **XOR** gates

- Circuit gates in $C_h \rightarrow$ Linear equations in G

$$\text{OR: } \boxed{x_1 \vee x_2} = y, z = x_1 \oplus x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$$

$$\text{XOR: } \boxed{x_1 \oplus x_2} = y, z = x_1 \wedge x_2 \iff \boxed{1y + 2z} - x_1 - x_2 = 0 \pmod{4}$$

$$G = \begin{pmatrix} \text{output gate} & \text{output wires} & 0 & 0 & 0 \\ 0 & \text{intermediate gate} & \text{intermediate wires} & 0 & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & \dots & \text{input gate} & \text{input wires} \end{pmatrix}$$

► $Gx_1 = 0 = Gx_2$ **represents** evaluation of $C_h(x_1)$ and $C_h(x_2)$

- x **contains** evaluation of $C_h(x)$ **gate-by-gate**
- $x = (\text{output}, \text{intermediate steps}, \text{input})^T$

$C_h \leq$ constrained-SIS – the A pt

A extracts the output of $C_h(x)$ from \mathbf{x}

$C_h \leq$ constrained-SIS – the \mathbf{A} pt

\mathbf{A} extracts the output of $C_h(x)$ from \mathbf{x}

- ▶ Set $\mathbf{A} = (1, 0, 0)$

$C_h \leq$ constrained-SIS – the \mathbf{A} pt

\mathbf{A} extracts the output of $C_h(x)$ from \mathbf{x}

- ▶ Set $\mathbf{A} = (1, 0, 0)$
- ▶ $\mathbf{x} = (\text{output}, \text{intermediate steps}, \text{input})^T$

$C_h \leq$ constrained-SIS – the \mathbf{A} pt

\mathbf{A} extracts the output of $C_h(x)$ from \mathbf{x}

- ▶ Set $\mathbf{A} = (1, 0, 0)$
- ▶ $\mathbf{x} = (\text{output}, \text{intermediate steps}, \text{input})^T$
- ▶ $\mathbf{Ax} = \text{output} \Rightarrow \mathbf{Ax} = C_h(x)$

$C_h \leq$ constrained-SIS – the \mathbf{A} pt

\mathbf{A} extracts the output of $C_h(x)$ from \mathbf{x}

- ▶ Set $\mathbf{A} = (1, 0, 0)$
- ▶ $\mathbf{x} = (\text{output}, \text{intermediate steps}, \text{input})^T$
- ▶ $\mathbf{Ax} = \text{output} \Rightarrow \mathbf{Ax} = C_h(x)$
- ▶ $\mathbf{Ax}_1 = \mathbf{Ax}_2$ implies $C_h(x_1) = C_h(x_2) \Rightarrow$ a collision for h ✓

$C_h \leq$ constrained-SIS – the \mathbf{A} pt

\mathbf{A} extracts the output of $C_h(x)$ from \mathbf{x}

- ▶ Set $\mathbf{A} = (1, 0, 0)$
- ▶ $\mathbf{x} = (\text{output}, \text{intermediate steps}, \text{input})^T$
- ▶ $\mathbf{Ax} = \text{output} \Rightarrow \mathbf{Ax} = C_h(x)$
- ▶ $\mathbf{Ax}_1 = \mathbf{Ax}_2$ implies $C_h(x_1) = C_h(x_2) \Rightarrow$ a collision for h ✓

Find Short Integer Solutions for $\mathbf{A}, \mathbf{G} \Rightarrow$ Find collisions in constrained-SIS
 \Rightarrow Find collision in C_h for any h
 \Rightarrow 

Series of reductions

Our result shows that:

SIS, LWE, SIVP, GapSVP, Minkowski, n-SVP, SHA, DLog, ... \leq constrained-SIS

These problems can be solved by finding collisions

Minkowski: $\|v\|_2 \leq \sqrt{n} \det(\mathcal{L})^{1/n}$

The post-quantum quest

A strong post-quantum guarantee for $\overset{\text{crown}}{h}$?

The post-quantum quest

A **strong post-quantum** guarantee for $\overset{\text{crown}}{h}$?

A quantum speedup for constrained-SIS

\iff quantum speedup for finding collisions, **in general**

The post-quantum quest

A **strong post-quantum** guarantee for $\overset{\text{crown}}{h}$?

A quantum speedup for constrained-SIS

\Leftrightarrow quantum speedup for finding collisions, **in general**

"Morally", a quantum speedup for lattice problems(?)

\Leftrightarrow quantum speedup for finding collisions, **in general**

The post-quantum quest

A **strong post-quantum** guarantee for $\overset{\text{crown}}{h}$?

A quantum speedup for constrained-SIS

\Leftrightarrow quantum speedup for finding collisions, **in general**

"**Morally**", a quantum speedup for lattice problems(?)

\Leftrightarrow quantum speedup for finding collisions, **in general**

This would be a **strong** implication. Should we expect this?

The post-quantum quest

A **strong post-quantum** guarantee for $\overset{\text{crown}}{h}$?

A quantum speedup for constrained-SIS

\Leftrightarrow quantum speedup for finding collisions, **in general**

"**Morally**", a quantum speedup for lattice problems(?)

\Leftrightarrow quantum speedup for finding collisions, **in general**

This would be a **strong** implication. Should we expect this?

This motivates the open problem section

- 🏆 A **worst-to-average** case reduction from constrained-SIS to itself?
- **Conjecture for h** : $\mathbf{A} \leftarrow \$$, $\mathbf{G} \leftarrow$ semi-random (random \star) experiments?

- 🏆 A **worst-to-average** case reduction from constrained-SIS to itself?
 - **Conjecture for h** : $\mathbf{A} \leftarrow \mathcal{S}$, $\mathbf{G} \leftarrow$ semi-random (random \star) experiments?
- ▶ approx-SVP/CVP **equivalent** to constrained-SIS?
 - approx-SVP/CVP are **fundamental** lattice problems
 - Minkowski short vectors & pigeonhole principle

Open problems

- 🏆 A **worst-to-average** case reduction from constrained-SIS to itself?
 - **Conjecture for h** : $\mathbf{A} \leftarrow \$$, $\mathbf{G} \leftarrow$ semi-random (random \star) experiments?
- ▶ approx-SVP/CVP **equivalent** to constrained-SIS?
 - approx-SVP/CVP are **fundamental** lattice problems
 - Minkowski short vectors & pigeonhole principle
- ▶ **Direct reduction** of specific hash functions to lattice problems?
 - $\text{SHA} \leq$ approx-SVP? \rightarrow **provable** security level?

Open problems

- 🏆 A **worst-to-average** case reduction from constrained-SIS to itself?
 - **Conjecture for h** : $\mathbf{A} \leftarrow \$, \mathbf{G} \leftarrow \text{semi-random (random } \star)$ experiments?
- ▶ approx-SVP/CVP **equivalent** to constrained-SIS?
 - approx-SVP/CVP are **fundamental** lattice problems
 - Minkowski short vectors & pigeonhole principle
- ▶ **Direct reduction** of specific hash functions to lattice problems?
 - $\text{SHA} \leq \text{approx-SVP?}$ → **provable** security level?
- ! **Structured lattices** in this framework? (e.g. ideal lattices)
 - ★ **understand** potential & limitations of structured lattices
 - 🏠 on structured lattices: more evidence for hardness, the better we sleep

...mathematical principles that guarantee a solution...

...mathematical principles that guarantee a solution...

- ▶ The **handshake lemma**. Given **undirected** graph $G(V, E)$:

$$\sum_{v \in V} \deg(v) = 2|E|$$

...mathematical principles that guarantee a solution...

- ▶ The **handshake lemma**. Given **undirected** graph $G(V, E)$:

$$\sum_{v \in V} \deg(v) = 2|E|$$

- ▶ A vertex with **odd** degree, implies **another vertex** with **odd** degree


...mathematical principles that guarantee a solution...

- ▶ The **handshake lemma**. Given **undirected** graph $G(V, E)$:

$$\sum_{v \in V} \deg(v) = 2|E|$$

- ▶ A vertex with **odd** degree, implies **another vertex** with **odd** degree
- ▶ **Hardness** in finding this **other odd degree** vertex

Complexity of factoring integers? in PPA [Jerábek '16]



- ▶ How low can Factoring go?
- ▶ Factoring \leq approx-SVP/CVP?

next: obfuscation!



modern crypto (we use it everyday)





A non-exhaustive list:

- ▶ Public-key encryption – (pk, sk) e.g. RSA
- ▶ Zero Knowledge Proofs
- ▶ Multiparty Computation
- ▶ Attribute-Based Encryption
- ▶ Fully-Homomorphic Encryption

...



A non-exhaustive list:

- ▶ Public-key encryption – (pk, sk) e.g. RSA
- ▶ Zero Knowledge Proofs
- ▶ Multiparty Computation
- ▶ Attribute-Based Encryption
- ▶ Fully-Homomorphic Encryption

...

Super-tool to build crypto tools?



A non-exhaustive list:

- ▶ Public-key encryption – ([pk](#), [sk](#)) e.g. RSA
- ▶ Zero Knowledge Proofs
- ▶ Multiparty Computation
- ▶ Attribute-Based Encryption
- ▶ Fully-Homomorphic Encryption

...

Super-tool to build crypto tools?

 Program Obfuscation


Program Obfuscation

Main character: programs

Goal: hide program secrets


What is obfuscation? (main character)

- ▶ An obfuscator is a **program compiler**




What is obfuscation? (main character \rightarrow obf)

- ▶ An obfuscator is a **program compiler**




What is obfuscation? (obf \rightarrow code)

- ▶ An obfuscator is a **program compiler**



What is obfuscation? (code hides secrets)


- ▶ An **obfuscator** is a **program compiler**



\tilde{P} hides implementation details of P
e.g. constants, variable values, procedures

Virtual Black-Box (VBB) security [Had00, BGI⁺01]

- ▶ An obfuscator is a **program compiler**



VBB security: only learn $(x, P(x))$

Obfuscation in practice

- *Heuristic* solutions (obfuscation as a product)
- International C code obfuscation (since 1984)

Obfuscation in practice

- *Heuristic* solutions (obfuscation as a product)
 - International C code obfuscation (since 1984)
-
- ▶ **Goal:** prove security based on a hard math problem
 - e.g. Lattice problems

Does VBB obfuscation exist?



Too good to be true?

Does VBB obfuscation exist?

- ▶ VBB obfuscation is **impossible** in the general case 😞

Does VBB obfuscation exist?



- ▶ VBB obfuscation is **impossible** in the general case 😊

Does VBB obfuscation exist?

- ▶ VBB obfuscation is **impossible** in the general case
- ▶ There is a program P we **cannot** VBB obfuscate

Does VBB obfuscation exist?

- ▶ VBB obfuscation is **impossible** in the general case
- ▶ There is a program P we **cannot** VBB obfuscate
- ▶ ...and a few programs that **can** be VBB obfuscated

Does VBB obfuscation exist?

- ▶ VBB obfuscation is **impossible** in the general case
- ▶ There is a program P we **cannot** VBB obfuscate
- ▶ ...and a few programs that **can** be VBB obfuscated
 - simple programs that predate our work
[Can97, Wee05, CD08, CRV10, BVWW16, Zha16]
point functions, hyperplanes, conjunctions

Does VBB obfuscation exist?

- ▶ VBB obfuscation is **impossible** in the general case
- ▶ There is a program P we **cannot** VBB obfuscate
- ▶ ...and a few programs that **can** be VBB obfuscated
 - simple programs that predate our work
[Can97, Wee05, CD08, CRV10, BVWW16, Zha16]
point functions, hyperplanes, conjunctions

❓ Can we obfuscate more programs ❓


- ▶ Wachs-Z FOCs'17
concurrent/independent GW'17
- Distribution-VBB obfuscate a large and expressive family of programs
- Most general result so far, provably secure under the Learning-with-Errors assumption

Compute-and-Compare programs (definition)


$$f(\cdot) \stackrel{?}{=} y$$

params: f, y, m


Compute-and-Compare programs (input)




Compute-and-Compare programs (output)



Compute-and-Compare programs (output)



CC obfuscation & security




Black-Box simulation security when y is **random** given f, m

Obfuscation **hides** params: f, y, m

Evasive programs

- ▶ if y is **random** given $f, m...$
- ▶ ...then for **most** $x \Rightarrow f(x) \neq y$
- ▶ why bother then?

Why obfuscate evasive programs?



New applications

- ▶ Hide the access policy: **upgrade** Attribute-based Encryption to Predicate Encryption
 - re-use existing ABE keys (modular approach)
- ▶ **Upgrade** Witness Encryption to null iO
- ▶ **Private** authentication using biometric data
- ▶ Obfuscate **conjunctions** under LWE

Post-quantum applications

some recent work 

- ▶ **Post-Quantum** Multi-Party Computation
[ABGKM, EUROCRYPT '21]
- ▶ **Post-Quantum** Zero-Knowledge in Constant Rounds
[Bitansky-Shmueli, STOC '20]
- ▶ Weak Zero-Knowledge
[Bitansky-Khurana-Paneth, STOC '19]
- ▶ Optimal Traitor-Tracing
[CVWWW, TCC '18]

optimized construction [GVW'18]

perfect correctness [GKVW'20]

Encrypt your own secret key: **Proofs** and **Heuristics**

A fundamental question [GM'84]

- ▶ Is $\text{Enc}(\text{pk}, \text{sk}_i)$ **always** secure?
 - **bit-by-bit** encryption of $\text{msg} = \text{sk}$

- ▶ We give a **negative** answer 😞
 - public-key **bit-by-bit CPA** secure \rightarrow circular **insecure**
(strong/non-pq assumptions [Rot13, KRW15])

- ▶ We **refute** a Random-Oracle **heuristic** for security of $\text{Enc}(\text{pk}, \text{sk}_i)$
 - the **only** heuristic transformation known

- ▶ Why investigate this type of security?

A fundamental question [GM'84]

- ▶ Is $\text{Enc}(\text{pk}, \text{sk}_i)$ **always** secure?
 - **bit-by-bit** encryption of $\text{msg} = \text{sk}$

- ▶ We give a **negative** answer 😞
 - public-key **bit-by-bit CPA** secure \rightarrow circular **insecure**
(strong/non-pq assumptions [Rot13, KRW15])

- ▶ We **refute** a Random-Oracle **heuristic** for security of $\text{Enc}(\text{pk}, \text{sk}_i)$
 - the **only** heuristic transformation known

- ▶ Why investigate this type of security?
 - Fundamental question
 - Recently in the news! (iO candidates)
 - ➔ Fully-Homomorphic Encryption (bootstrapping)

Can Random Oracles help?

- ▶ Random Oracles (RO) are used both in theory and practice
 - Publicly accessible *gigantic* source of randomness
 - i.e. $RO(x) = \text{random}$
- ▶ In practice, replacing $RO = \text{SHA-2/SHA-3}$
- ▶ In theory, replacing $RO = \text{it's complicated}$

Can Random Oracles really help?

Power of RO 

- ▶ Transform **any** IND-CPA scheme to a circular secure one [BRS03]
- ▶ $\text{Enc}_{\text{RO}}(\text{pk}, m) = \text{Enc}(\text{pk}, r), \text{RO}(r) \oplus m$

Can Random Oracles really help?

Power of RO

- ▶ Transform **any** IND-CPA scheme to a circular secure one [BRS03]
- ▶ $\text{Enc}_{\text{RO}}(\text{pk}, m) = \text{Enc}(\text{pk}, r), \text{RO}(r) \oplus m$

Power of obfuscation

- ▶ We construct an IND-CPA scheme that **cannot** be upgraded as above...
...no matter which hash function is used to implement RO

Circular insecurity: $\text{sem} \rightarrow \text{circ-insec}$

Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

public key: $\text{Enc}(\text{pk}, \cdot)$



Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

public key: $\text{Enc}(\text{pk}, \cdot)$

$$y \leftarrow \$$$

► $\text{sk}' \rightarrow (\text{sk}, y)$

Circular insecurity: $\text{sem} \rightarrow \text{circ-insec}$

Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

$$y \leftarrow \$$$

► $\text{sk}' \rightarrow (\text{sk}, y)$

public key: $\text{Enc}(\text{pk}, \cdot)$

$$\text{Dec}_{\text{sk}}(\cdot) \stackrel{?}{=} y$$

params: sk, y, sk

► $\text{pk}' \rightarrow (\text{pk}, \text{Obf})$

Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

$$y \leftarrow \$$$

▶ $\text{sk}' \rightarrow (\text{sk}, y)$

public key: $\text{Enc}(\text{pk}, \cdot)$

$$\text{Dec}_{\text{sk}}(\cdot) \stackrel{?}{=} y$$

params: sk, y, sk

▶ $\text{pk}' \rightarrow (\text{pk}, \text{Obf})$

▶ y indep of $\text{sk} \Rightarrow$ semantic security

Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

$$y \leftarrow \$$$

► $\text{sk}' \rightarrow (\text{sk}, y)$

public key: $\text{Enc}(\text{pk}, \cdot)$

$\text{Enc}_{\text{pk}}(y) \rightarrow$

$$\text{Dec}_{\text{sk}}(\cdot) \stackrel{?}{=} y$$

params: sk, y, sk

$\rightarrow \text{sk}$

► $\text{pk}' \rightarrow (\text{pk}, \text{Obf})$

► y indep of $\text{sk} \Rightarrow$ semantic security

Assume bit encryption

secret key: $\text{Dec}(\text{sk}, \cdot)$

$$y \leftarrow \$$$

▶ $\text{sk}' \rightarrow (\text{sk}, y)$

public key: $\text{Enc}(\text{pk}, \cdot)$

$\text{Enc}_{\text{pk}}(y) \rightarrow$

$$\text{Dec}_{\text{sk}}(\cdot) \stackrel{?}{=} y$$

params: sk, y, sk

$\rightarrow \text{sk}$

▶ $\text{pk}' \rightarrow (\text{pk}, \text{Obf})$

▶ y indep of $\text{sk} \Rightarrow$ semantic security

☠ recover $\text{sk} \Rightarrow$ break security!

Random Oracles: real vs ideal

- ▶ GKW'17 shows similar result for Fujisaki-Okamoto
- ▶ **Caution:** RO Model \rightarrow Standard Model (SHA-3, ...)
- ▶ **Ideally**, we wouldn't need RO
 - comparable efficiency without RO?

is obfuscation a success story?

is obfuscation a success story?

- ▶ "relaxed" form of obfuscation \Rightarrow almost all crypto 👍
- ▶ indistinguishability **O**bfuscation
- ▶ **iO** most probably exists as of 2021 (**non-pq**)! [..., JLS'21, ...]
- ▶ other new constructions involve new **circular security** definitions

is obfuscation a success story?

- ▶ "relaxed" form of obfuscation \Rightarrow almost all crypto 👍
- ▶ indistinguishability **O**bfuscation
- ▶ **iO** most probably exists as of 2021 (**non-pq**)! [..., JLS'21, ...]
- ▶ other new constructions involve new **circular security** definitions

tales of **iO**

- ▶ Cryptographic hardness of NASH equilibria [AKV'05, BPR'15]
- ▶ 2-Round Multiparty Computation [GGHR'14, GP'15]
- ▶ Program Watermarking [CHNVW '16]
 - Quach-Wichs-**Z** TCC'18
- ...

is obfuscation a success story?

tales of **iO**

- ▶ "relaxed" form of obfuscation \Rightarrow almost all crypto 
 - ▶ indistinguishability **O**bfuscation
 - ▶ **iO** most probably exists as of 2021 (**non-pq**)! [..., JLS'21, ...]
 - ▶ other new constructions involve new **circular security** definitions
-
- ▶ Cryptographic hardness of NASH equilibria [AKV'05, BPR'15]
 - ▶ 2-Round Multiparty Computation [GGHR'14, GP'15]
 - ▶ Program Watermarking [CHNVW '16]
 - Quach-Wichs-**Z** TCC'18
 - ...

$$a(b + c)$$

\approx

$$ab + ac$$



Recent work – future post-quantum directions

- ▶ Adaptive prefix encryption under LWE (**Z '21**)
 - prefix enc = original Hierarchical IBE
 - algebraic instead of bb IBE use – focus on params
 - 🏆 ...but "really adaptive" post-quantum HIBE **still** open (EUROCRYPT '10 [ABB10, CHKP10])
 - pairings **superior to** lattices

Recent work – future post-quantum directions

- ▶ Adaptive prefix encryption under LWE (**Z '21**)
 - prefix enc = original Hierarchical IBE
 - algebraic instead of bb IBE use – focus on params
 - 🏆 ...but "really adaptive" post-quantum HIBE **still** open (EUROCRYPT '10 [ABB10, CHKP10])
 - pairings **superior to** lattices
- ▶ (Zero-Knowledge) Proofs, Obfuscation (iO), FHE
 - very active for **post-quantum** – theory & practice

Recent work – future post-quantum directions

- ▶ Adaptive prefix encryption under LWE (**Z '21**)
 - prefix enc = original Hierarchical IBE
 - algebraic instead of bb IBE use – focus on params
 - 🏆 ...but "really adaptive" post-quantum HIBE **still** open (EUROCRYPT '10 [ABB10, CHKP10])
 - pairings **superior to** lattices
- ▶ (Zero-Knowledge) Proofs, Obfuscation (iO), FHE
 - very active for **post-quantum** – theory & practice
- ★ **Structured** lattices: new techniques/algorithms?
 - **efficient ZK** → **new** ideas

Recent work – future post-quantum directions

- ▶ Adaptive prefix encryption under LWE (**Z '21**)
 - prefix enc = original Hierarchical IBE
 - algebraic instead of bb IBE use – focus on params
 - 🏆 ...but "really adaptive" post-quantum HIBE **still** open (EUROCRYPT '10 [ABB10, CHKP10])
 - pairings **superior to** lattices
- ▶ (Zero-Knowledge) Proofs, Obfuscation (iO), FHE
 - very active for **post-quantum** – theory & practice
- ★ **Structured** lattices: new techniques/algorithms?
 - **efficient ZK** → **new** ideas
- ▶ IBE/ABE followed after PKE. Next primitive to _____ ?

Recent work – future post-quantum directions

- ▶ Adaptive prefix encryption under LWE (**Z '21**)
 - prefix enc = original Hierarchical IBE
 - algebraic instead of bb IBE use – focus on params
 - 🏆 ...but "really adaptive" post-quantum HIBE **still** open (EUROCRYPT '10 [ABB10, CHKP10])
 - pairings **superior to** lattices
- ▶ (Zero-Knowledge) Proofs, Obfuscation (iO), FHE
 - very active for **post-quantum** – theory & practice
- ★ **Structured** lattices: new techniques/algorithms?
 - **efficient ZK** → **new** ideas
- ▶ IBE/ABE followed after PKE. Next primitive to _____ ?
- ♥ LWR, LPN

Thank you!

```
char
_3141592654[3141
],__3141[3141];_314159[31415];_3141[31415];main(){register char*
_3_141,*_3_1415,*_3__1415; register int _314,_31415,__31415,*_31,
_3_14159,__3_1415;*_3141592654=_31415*2,_3141592654[0][_3141592654
-1]=1[_3141]=5;__3_1415=1;do{__3_14159=_314*0,__31415++;for( _31415
=0;_31415<(3,14-4)*__31415;_31415++)_31415[_3141]=_314159[_31415]= -
1;_3141[*_314159-_3_14159]=_314;_3_141=_3141592654+__3_1415;_3_1415=
__3_1415 +__3141;for (_31415 = 3141-
__3_1415 ; _31415=_31415-_31415--
,_3_141 ++, _3_1415++){_314
+*_314<<2 ; _314<<=1;_314+=
*_3_1415;_31 _314159+_314;
if(!(*_31+1) )*_31 =_314 /
__31415,_314 [_3141]=_314 %
__31415;*( _3_1415=_3_141
) += *_3_1415 = *_31;while(*
_3__1415 >= 31415/3141 ) *
_3_1415+= - 10,(+--_3_1415
)++;_314=_314 [_3141]; if ( !
_3_14159 && * _3_1415)_3_14159
=1,__3_1415 = 3141-_31415;if(
_314+(__31415 >>1)>__31415 )
while ( ++ * _3_141==3141/314
)*_3_141--=0 ;}while(_3_14159
); { char * __3_14=" 3.14159";
write((3,1), (-+__3_14,__3_14
),( _3_14159 ++,+__3_14159))+
3.1415926; } for ( _31415 = 1;
_31415<3141- ++,_31415++)write(
31415% 314-( 3,14) ,_3141592654[
_31415 ] + "0123456789","314"
[ 3]+1)-_314; puts((*_3141592654=0
,_3141592654)); _314= *_3.141592";}
```

6th International Obfuscated C Code Contest (1989)